

**IN THE CLAIMS:**

Please amend the claims as follows:

1. (Previously Presented) An apparatus for storage of information, comprising:  
magnetic ink, including a magnetic substance, said magnetic ink having a stored information signal.
2. (Original) The magnetic ink of claim 1, wherein the stored information signal includes an analog information signal.
3. (Original) The magnetic ink of claim 1, wherein the stored information signal includes a digital information signal.
4. (Original) The magnetic ink of claim 1, wherein the stored information signal includes a time-varying frequency signal.
5. (Original) A magnetic information storage structure, comprising:  
a surface; and  
magnetic ink applied to the surface, said magnetic ink magnetized such as to contain an encoded information signal.
6. (Original) A magnetic ink encoding stylus, comprising:  
a penpoint adapted to apply magnetic ink to a surface; and  
a magnetic ink write head, coupled to the penpoint and adapted to apply a varying magnetic flux to the magnetic ink as it is applied by the penpoint to the surface.
7. (Currently Amended) ~~The apparatus of claim 6,~~ A magnetic ink encoding stylus,  
comprising:  
a penpoint adapted to apply magnetic ink to a surface; and

a magnetic ink write head, coupled to the penpoint and adapted to apply a varying magnetic flux to the magnetic ink as it is applied by the penpoint to the surface  
wherein the magnetic ink write head includes:

a magnetic field generator, and  
a magnetic shield.

8. (Original) The apparatus of claim 7, wherein the magnetic field generator includes a magnetic coil.

9. (Original) The apparatus of claim 8, wherein the magnetic coil is a wire coil.

10. (Original) The apparatus of claim 7, further comprising a magnetic field director.

11. (Original) The apparatus of claim 10, wherein the magnetic field director includes an iron core element.

12. (Original) The apparatus of claim 6, wherein the magnetic ink write head includes a plurality of magnetic pole faces.

13. (Original) The apparatus of claim 6, further comprising a signal generator coupled to the magnetic ink write head.

14. (Original) The apparatus of claim 13, wherein the signal generator includes a analog timing signal generator.

15. (Original) The apparatus of claim 13, wherein the signal generator includes a digital signal generator.

16. (Original) The apparatus of claim 13, further comprising a pressure sensor coupled to the signal generator.

17. (Original) The apparatus of claim 6, further comprising encoding electronics coupled to the magnetic ink write head.

18. (Original) The apparatus of claim 17, further comprising a direction sensor coupled to the encoding electronics.

19. (Original) The apparatus of claim 6, further comprising a port adapted to be coupled to an external computer bus, said port coupled to the magnetic ink write head.

20. (Original) A computer system, comprising:

a computer, including

a processor;

a memory coupled to the processor; and

an external bus coupled to the processor; and

a magnetic ink encoding stylus, including

a penpoint adapted to apply magnetic ink to a surface;

a magnetic ink write head coupled to the penpoint and

adapted to apply a varying magnetic flux to the magnetic ink as it is applied by the penpoint to the surface; and

a port coupled to the magnetic ink write head and to the external bus.

21. (Original) The computer system of claim 20, wherein the magnetic ink encoding stylus includes a signal generator.

22. (Original) The computer system of claim 20, wherein the magnetic ink encoding stylus includes encoding electronics.

23. (Original) The computer system of claim 20, wherein the computer includes:  
a graphics tablet coupled to the processor; and  
a handwriting recognition application coupled to the processor.

24. (Currently Amended) A method of storing information, comprising:  
applying magnetic ink on a surface; and  
applying a varying magnetic flux to the magnetic ink to store information  
in said magnetic ink.

25. (Original) The method of claim 24, wherein the information is digital information signal.

26. (Original) The method of claim 24, wherein the information is security data.

27. (Original) The method of claim 24, wherein applying a varying magnetic flux to the applied magnetic ink includes:  
generating a varying magnetic field corresponding to an information signal, the varying magnetic field intersecting the applied magnetic ink.

28. (Original) The method of claim 27, further comprising:  
responsive to sensing stylus pressure, generating the information signal.

29. (Original) The method of claim 27, wherein the information signal is a timing signal.

30. (Original) The method of claim 27, wherein the information signal is received from a computer.